

Fusion Power Boats - Tech Specs / Base Inclusions & Accessories

Fusion 15

Specifications

- LOA 4.6 m
- BOA 2 m
- Draft 280 mm
- 16 Degree deadrise
- 15 Degree transom
- 520 mm Transom height
- Electric trolling motor 60 pound thrust and 60 inch shaft length
- Min HP – 30 HP
- Max HP – 70 HP
- GRP construction
- Wet deck
- 130% CAT D Buoyancy
- Single engine installation
- SAMSA CAT R – 6 PAX = 450 kg
- SAMSA CAT E – 4 PAX = 300 kg
- SAMSA CAT D – 2 PAX = 150 kg

Base model includes:

- Boat on trailer 13 in wheels
- Galvanised axle
- Helm seat and bolster
- Helm forward seat
- Helm grab handles
- Gunwale grab handles
- Bow seat
- Anchor locker
- Live bait well
- Railblaza starports
- Service locker
- Wet deck

Accessories available:

- Fusion 15 brake neck upgrade
- 14 in Tyre and mudguard upgrade
- Fold away boom extension
- Optional hull colour gel coat

- Transom step plain no ladder (white)
- Transom step with telescopic ladder (white)
- Transom step plain no ladder (colour coded)
- Transom step with telescopic ladder (colour coded)
- Extra Railblaza starports x 1
- Helm and seat cover
- Boat cover
- Square tube strut
- Rule live bait system
- Fusion 15 Ski Bar
- Flexiteek decking