

# Fusion Power Boats - Tech Specs / Base Inclusions & Accessories

## Fusion 17

### Specifications

- LOA 5.4 m
- BOA 2.1 m
- Freeboard 500 mm
- Draft 280 mm – 330 mm (HP Dependent)
- 16 Degree deadrise
- 15 Degree transom
- 540 mm Transom height
- Electric trolling motor 80 pound thrust 60 in shaft
- Min HP – 60 HP
- Max HP – Twin HP 2 x 30 HP or 2 x 40 HP
- GRP construction
- Wet deck
- 154% CAT C Buoyancy
- Single or dual engine installation
- SAMSA CAT R – 7 PAX
- SAMSA CAT E – 4 PAX
- SAMSA CAT D – 4 PAX
- SAMSA CAT C – 3 PAX

### Base model includes:

- Boat on trailer 14 in wheels
- Galvanised axle
- Stainless brake system
- Hub flush out ports
- Helm seat and bolster
- Helm forward seat
- Helm grab handles
- Gunwale grab handles
- Bow V seating with gas strut lockers
- Anchor locker
- Live bait well
- Railblaza starports
- Service locker
- Wet deck

### Accessories available:

- Fusion 17 brake neck upgrade
- Bolt on guide arms with PVC tubing
- 15 in Tyre, mudguard, axle upgrade
- Optional hull colour gel coat
- Casting platform
- Transom step plain no ladder (white)
- Transom step with telescopic ladder (white)
- Transom step plain no ladder (colour coded)
- Transom step with telescopic ladder (colour coded)
- Extra Railblaza starports x 1
- T-top aluminium
- Folding t-top
- Square tube strut type sun-canopy
- Helm and seat cover
- Boat cover
- Forward seat cushions x 3
- Forward sunbed cushion x 1
- Fusion 17 ski bar
- Rule live bait system
- Flexiteek decking