

Fusion Power Boats - Tech Specs / Base Inclusions & Accessories

Fusion 19

Specifications

- LOA 5.97 m
- BOA 2.4 m
- Freeboard 680 mm
- 18 Degree deadrise at transom
- 15 Degree transom
- 350 mm Daft
- Single or dual engine installation
- Electric trolling motor 105 /115 pound - 60/70 in shaft
- Single motor: 25 in XL transom height
- Twin motor: 20 in L transom height
- Min HP – Single 130 HP / Twin 50 HP
- Max HP – Single 200 HP / Twin 70 HP
- GRP construction
- Wet deck
- 130% Cat C Buoyancy
- SAMSA Cat R – B
- LOA on trailer with motor up – 8290 mm
- LOA on trailer with motor down – 7810 mm
- HOA overall on trailer 14 in wheels – 2375 mm

Base model includes:

- Boat on trailer 14 in wheels
- Galvanised axle
- Stainless brake system
- Hub flush out ports
- Helm seat and bolster
- Helm forward seat
- Helm grab handles
- Gunwale grab handles
- Fwd under deck locker
- Aft under deck locker
- Bow V seating with gas strut locker lids
- Anchor locker
- Live bait well
- Railblaza starports
- Service locker
- Wet deck

Accessories available:

- Breakneck upgrade
- Bolt on guide arms with PVC tubing
- 15 in Tyres, mudguards, axle upgrade
- Optional hull colour gel coat
- Casting platform
- Casting platform with storage lockers
- 150 L Built-in fuel tank-sender, deck filler, breather x 1
- Flexiteek decking
- Transom step plain no ladder (white)
- Transom step with telescopic ladder (white)
- Transom step plain no ladder (colour coded)
- Transom step with telescopic ladder (colour coded)
- Extra Railblaza starports x 1
- T-top aluminium
- Helm seat cover
- Boat cover
- Forward seat cushions x 3
- Forward sunbed cushion x 1
- Aft seat cushions x 2
- Ski bar single engine
- Ski bar twin engine
- Rule live bait system
- Black powder coating
- 78 L Cooler box system
- Salt water deck wash system
- Fresh water shower system with 50 L tank